



Chemical Protection

XPOSURE GUARD™ C2 Protective Outer Wear

We've got you covered. To learn more, give us a call:

334-899-4351

Chemical Challenge	CAS#	Test Method	Xposure Guard C2- Saranex 23P Laminate
Acetonitrile	75-05-8	ASTM F739	41 minutes
Ammonia Liquid 30%	7664-41-7	ASTM F739	>480 minutes
Black Liquor	66071-92-9	ASTM F739	>480 minutes
Crude Oil	Mixture	ASTM F739	>480 minutes
Diesel Automotive Test Fuel	68476.34-6	ASTM F739	>480 minutes
Diesel Fuel	68476-34-6	ASTM F739	>480 minutes
Diesel Fuel, Ultra Low Sulfur	68476-34-6	ASTM F739	>480 minutes
Diethylamine	109-89-7	ASTM F739	17 minutes
Dimethylformamide	68-12-2	ASTM F739	>480 minutes
Ethanol	64-17-5	ASTM F739	>480 minutes
Ethylene Glycol	107-21-1	ASTM F739	>480 minutes
Gasoline	8006-61-9	ASTM F739	6 minutes
Green Liquor	68131-30-6	ASTM F739	>480 minutes
Hydrochloric Acid	7647-01-0	ASTM F739	>480 minutes
Hydrogen Peroxide 70%	7722-84-1	ASTM F739	>480 minutes
Isopropanol	67-63-0	ASTM F739	>480 minutes
Jet Fuel A	8008-20-6	ASTM F739	>480 minutes
Jet Fuel JP4	8008-20-6	ASTM F739	>480 minutes
Jet Fuel JP8	8008-20-6	ASTM F739	>480 minutes
Methanol	67-56-1	ASTM F739	>480 minutes
Methyldiethanolamine	105-59-9	ASTM F739	>480 minutes
Mineral Oil	8042-47-5	ASTM F739	>480 minutes
Mineral Spirits	64475-85-0	ASTM F739	20 minutes
Naphtha, Alkylate	64741-64-6	ASTM F739	>480 minutes
Naphtha, Full Range	64741-42-0	ASTM F739	8 minutes
Naphtha, Isomereate	64741-70-4	ASTM F739	>480 minutes
Naphtha, Reformate	64741-63-5	ASTM F739	3 minutes
Nitric Acid 70%	7697-37-2	ASTM F739	>480 minutes
Nitrobenzene	98-95-3	ASTM F739	112 minutes
Phenol @43C	108-95-2	ASTM F739	440 minutes
Phosphoric Acid	7664-38-2	ASTM F739	>480 minutes
Potassium Hydroxide	1310-58-3	ASTM F739	>480 minutes
Sodium Hydroxide	1310-73-2	ASTM F739	>480 minutes
Sodium Hypochlorite 15%	7681-52-9	ASTM F739	>480 minutes
Sulfuric Acid	7664-93-9	ASTM F739	>480 minutes
White Liquor	68131-33-9	ASTM F739	>480 minutes

*imm-immediate breakthrough, NT-Not Tested.

It is the user's responsibility to read and understand all provided warnings, proper usage, and care information. This garment and/or fabric is Not Suitable for use with some chemicals and hazardous agents. Contact your employer on specific chemicals and agents. It is the user's responsibility to determine the level of risk and proper personal protection equipment needed because conditions of use are outside of garment manufacturer control. Garment Manufacturer makes no warranties, expressed or implied, and assumes no liability as to the suitability of this product for a particular use.